Appl. No. 10/005,497 Amdt. dated 16 June 2004

Reply to Office action of 18 December 2003

Attorney Docket No. 26.0206

Page 2 of 10

This listing of claims will replace all prior version, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method of determining the sonic slowness of a formation traversed by a borehole comprising:

generating tracks from sonic waveform peaks received at a plurality-of-more than two depths; and

classifying the generated tracks, wherein the waveform peaks are not elassified step of classifying is not performed prior to the step of generating trackstracking.

- 2. (currently amended) The method of claim 1 wherein the step of generating classifying the generated tracks comprises classifying long tracks; classifying small tracks; classifying tracks that overlap; filling in gaps; and creating a final log.
- 3. (original) The method of claim 2, wherein said filling in gaps further comprises using non-classified tracks to fill gaps.
- 4. (original) The method of claim 2, wherein said filling in gaps further comprises performing interpolation.
- 5. (original) The method of claim 4, wherein said interpolation is linear.
- 6. (previously presented) The method of claim 5 wherein linear interpolation is done if the gaps are less than 6 frames.
- 7. (original) The method of claim 3, wherein filling in gaps further comprising performing interpolation.

Appl. No. 10/005,497 Amdt. dated 16 June 2004 Reply to Office action of 18 December 2003

Attorney Docket No. 26.0206

Page 3 of 10

- 8. (original) The method of claim 1, wherein tracks are considered as individual objects comprising peaks.
- 9. (original) The method of claim 8 wherein said peaks are defined using semblance, time and slowness.
- 10. (original) The method of claim 9 wherein only time and slowness are used for classification.
- 11. (original) The method of claim 10, wherein a probability of a track being one of a compressional and shear is determined using all points forming the track.
- 12. (original) The method of claim 11, wherein classification of one track is independent of classification of a track different from said one track.
- 13. (original) The method of claim 2, wherein step of classifying the long tracks further comprises:

fitting a distribution function on peaks of the track;

calculating a mean and variance of the distribution;

comparing distribution of the data with a distribution of a model data; and

classifying the long track according to the model data if said comparison

determines that the track data and model data are consistent.

14. (original) The method of claim 2 wherein step of classifying the short tracks further comprises:

computing a 2-D median of the track, said median being a point defined by corresponding coordinates in a slowness and time domain;

determining an intersection of the slowness and time domain with a model data distribution;

defining the model in the slowness and time domain as an ellipse; and classifying the small track based on a position of the peak in relation to the model data.

Appl. No. 10/005,497 Amdt. dated 16 June 2004 Reply to Office action of 18 December 2003 Attorney Docket No. 26.0206

Page 4 of 10

15. (original) The method of claim 2, wherein step of filling in the gaps further comprises:

determining if there is a gap in a selected track at a depth range covered by the selected non-classified track;

deleting the track if no gap is found; and

filling the gap in the selected track after determining that the selected nonclassified track can be used to fill the gap.

- 16. (original) The method of claim 15, wherein said determining if the selected track can be used to fill the gap is done by evaluating if the selected track is between upper part and lower part of a skeleton, wherein said skeleton comprises tracks that have been classified so far.
- 17. (original) The method of claim 2, wherein said long track comprises more than 20 frames.
- 18 (original) The method of claim 2, wherein said small track comprises less than or equal to 20 frames.
- 19. (original) The method of claim 14, wherein said model is one of a compressional model and shear model.
- 20. (original) The method of claim 13 wherein slowness and time are treated having Gaussian probability distribution.
- 21. (original) The method of claim 20 wherein 2D Gaussian probability distribution of slowness and time is measured at one depth based on measurements at a previous depth.
- 22. (original) The method of claim 20 wherein said measurement is done by a 2D Kaman filter process.

6/ 13

Appl. No. 10/005,497 Amdt. dated 16 June 2004 Reply to Office action of 18 December 2003 Attorney Docket No. 26,0206 Page 5 of 10

23. (currently amended) A computer system for performing a method of determining the sonic slowness of a formation traversed by a borehole comprising: generating tracks from sonic waveform peaks received at-a plurality-of two or more depths; and

classifying the generated tracks, wherein the waveform peaks are not elassified step of classifying is not performed prior to the step of generating trackstracking, wherein said method-step of classifying tracks comprises classifying long tracks, classifying small tracks, classifying tracks that overlap, filling in gaps and creating a final log, wherein the method is implemented in a program stored on a storage media and the output is applied to at least one output device.

- 24. (currently amended) A method of determining the sonic slowness of a formation traversed by a borehole comprising generating tracks from sonic waveform peaks received at a plurality of depths, comprising
- a) classifying long tracks of greater than 20 frames, further comprising fitting a distribution function on peaks of the track; calculating a mean and variance of the distribution; comparing distribution of the data with a distribution of a model data; and classifying the long track according to the model data if said comparison determines that the track data and model data are consistent:
- b) classifying small tracks of less than or equal to 20 frames, further comprising computing a 2-D median of the track, said median being a point defined by corresponding coordinates in a slowness and time domain; determining an intersection of slowness and time domain with a model data distribution; defining the model in the slowness and time domain as an ellipse; and classifying the small track based on a position of the peak in relation to the model data;
- c) classifying tracks that overlap, wherein said steps of classifying long tracks, small tracks and tracks that overlap are not performed prior to tracking of sonic waveform peaks received at more than two depths;
- d) filling in the gaps, further comprising determining if there is a gap in a selected track at a depth range covered by a selected non-classified track; deleting the

Appl. No. 10/005,497 Amdt. dated 16 June 2004 Reply to Office action of 18 December 2003 Attorney Docket No. 26.0206

Page 6 of 10

track if no gap is found; and filling the gap in the selected track after determining that the selected non-classified track can be used to fill the gap; and

e) creating a final log.